



Features

- Wideband, DC to 60 GHz
- High Power Handling, 2 W
- Excellent Return Loss
- 1.5x1.5 mm, 6-Lead QFN-Style Package
- Human Body Model (HBM): Class 2 (> 2000 V)
- Charged Device Model (CDM): Class C3 (≥1000V)
- Moisture Sensitivity: MSL1




Applications

- Test & Measurement Equipment
- Satellite Communications
- Radar, EW, and ECM Defense Systems
- Telecom Infrastructure
- 5G sub-6 GHz and mmW


Electrical specifications at 25°C

Parameter	Frequency (GHz)	Min.	Typ.	Max.	Units
Frequency Range		DC		60	GHz
Attenuation	0.01-10 10-20 20-30 30-40 40-50 50-60		0.05 0.13 0.28 0.32 0.42 0.52	0.6 0.9 1.1 1.3	dB
Input Return Loss	0.01-10 10-20 20-30 30-40 40-50 50-60		34 26 20 21 22 24		dB
Output Return Loss	0.01-10 10-20 20-30 30-40 40-50 50-60		34 26 20 21 22 24		dB
Input RF Power			2		W
Operating & Storage Condition Operation Temperature Range: -45°C to +105°C Storage Temperature Range: -65°C ~ +150°C					

Outline Drawing (Units= mm [inches])



PCB Land Pattern (Units= mm [inches])




Suggested Layout,
Tolerance to be within ± 0.050 mm

NOTES:

1.  DENOTES METALLIZATION

Functional Diagram



Function	Pad Number
RF-IN	2
RF-OUT	5
GND	1, 3, 4, 6 & Paddle

Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com